

COMMERCIALON PREMIUM ADHESIVE FOR MODULAR CARPET AND LVT

Page 1 of 5

1. Identification

Manufactured exclusively for:

J&J Flooring	Pentz Commercial	Manufactured by:"
818 J&J Drive	3510 Corporate Dr.	Mapei
Dalton, GA 30721	Dalton GA 30721	1144 E. Newport Center Drive
		Deerfield Beach, FL 33442

Emergency phone USA (CHEMTREC): 800-424-9300" (CHEMTREC INTERNATIONAL): 703-527-3887

Industrial Health/Spill Emergency: 800-424-9300 (Chemtrec)
Information phone: J+J Flooring - 706-529-2100 or Pentz Commercial - 866-706-9745 x8407.

Date Printed: 09/23/2013
Date Revised: N/A
Supersedes: N/A

Usage: Industrial

2. Hazard(s) Identification

May cause irritation of the skin and eyes. May be an inhalation and ingestion hazard.
This product is not for human consumption.

3. Composition/Information on Ingredients

Information on hazardous ingredients: No toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and/or 40 CFR 372 are present.

Chemical name:	Aqueous Adhesive	%w/w	
Product code:	N/A	Hazard symbol:	N/A
CAS-no.:	Mixture	H-phrases:	N/A
EC-no.:	N/A	P-phrases:	P273
Formula:	No information available		

See section 16 for the full text of the Hazard symbols and phrases.

4. First Aid Measures

Inhalation:	If affected, remove to fresh air and consult medical attention from a healthcare professional.
Skin Contact:	Wash with soap and water.
Eye Contact:	Flash eyes immediately with plenty of water for 15 minutes, including upper and lower eyelids. Washing eyes within one minute is essential to achieve maximum effectiveness. Remove contact lenses after the first 5 minutes. Obtain medical attention from a healthcare professional if irritation persists.
Ingestion:	Never give anything by mouth if victim is unconscious or having convulsions; seek medical attention from a healthcare professional. Do not induce vomiting unless directed to do so by medical personnel.

COMMERCIALON PREMIUM ADHESIVE FOR MODULAR CARPET AND LVT

5. Fire-Fighting Measures Page 2 of 5

Suitable extinguishing media: Chemical Foam, CO2, Water Fog

Hazardous decomposition/combustion products:
 Thermal decomposition should produce only normal Hydrocarbon combustion products. Products of thermal decomposition may be harmful.

Special protective equipment for fire fighters:
 None; this product is non-flammable in aqueous form (as supplied).

Other information: None known; non-combustible and non-explosive as supplied. If ignited by excessive heat or open flame, this product will burn. Burning material may emit toxic fumes. Fire fighters should wear NIOSH-approved self-contained breathing apparatus with full face piece, operated in positive pressure mode. Wear full firefighting protective clothing. Use water fog to cool containers exposed to extreme heat.

6. Accidental Release Procedures

Personal precautions: Use caution to avoid slipping in wet adhesive.

Environmental precautions: Dike and contain spill for possible recovery and to prevent from entering waterways.

Methods for cleaning/taking up:
 Recover as much as possible; wash floors afterwards with water.
 Smaller spills may be wiped from surfaces or absorbed onto inert material and handled as solid waste. Do not allow material into sewers, on the ground or into any body of water. Must be disposed of in accordance with all local, state, federal and international regulations.

7. Handling and Storage

Adhere to work practice rules established by government regulations (e.g. OSHA)

Advice on protection against fire and explosion: None known.

Storage requirements:
 Use reasonable care to avoid skin and eye contact. Keep containers closed when not in use. Protect containers against physical damage. Store in a cool (4°- 43°C/43° -110°F), dry, well-ventilated area inside. Do not allow product to freeze.

8. Exposure Controls/
 Personal Protection

Exposure limits: Personal protection: Hand protection: Eye protection: Skin and body:	No information available. Consult local authorities for acceptable exposure limits. None necessary under normal conditions (adequate ventilation). Recommended local exhaust. None needed under normal conditions. If contact is expected, wear impervious gloves. If splashing is likely, wear safety glasses. None needed under normal use conditions. Use reasonable care to avoid contact.
---	--

COMMERCIALON PREMIUM ADHESIVE FOR MODULAR CARPET AND LVT

9. Physical and Chemical Properties		Page 3 of 5
Form:	Water-based, viscous liquid	
Color:	Blue	
Odor:	Mild, characteristic	
Boiling point/range:	100°C/212° F	
Melting Point/range:	No information available	
Flash point:	No flash	
Flammability:	No information available	
Autoignition temperatures:	No information available	
Explosion limits:	N/A	
Vapor pressure:	N/A	
Weight per Gallon	8.3 typical	
Solubility in water:	Insoluble	
Solubility in other solvents:	No information available	
pH:	8.0 - 9.0	
Partition coefficient:	No information available	
n-octanol/water:	No information available	

10. Stability and Reactivity	
Conditions to avoid:	Stable. Avoid freezing. Hazardous polymerization will not occur.
Materials to avoid:	None known.
Hazardous decomposition products:	Thermal decomposition should produce only normal hydrocarbon combustion products.
Products of thermal decomposition may be harmful.	

11. Toxicological Information	
Acute Toxicity data: Oral LD50:	No information available
Dermal LD50:	No information available
Inhalation LC50:	No information available
Irritation: Skin:	Irritant
Eye:	Irritant
Sensitization:	No information available
Genotoxicity:	No information available
Other toxicological information:	No information available

12. Ecological Information	
Fish:	No information available
Daphnia:	No information available
Algae:	96h-EC50 (Cell count): No information available.

13. Disposal Considerations	
Product:	Do not allow material into sewers, on the ground or into any body of water. Must be disposed of in accordance with all local, state, federal and international regulations.
Packaging:	No information available
Waste code number:	Please refer to your specific industry in the European Waste catalog.

COMMERCIALON PREMIUM ADHESIVE FOR MODULAR CARPET AND LVT

16. Other Information:

Page 5 of 5

Hazardous Material Identification System (HMIS) rating/codes:

Health-1 Flammability-0 Reactivity-0 Protective Equipment-B (safety eyewear, gloves)

HMIS uses a numbering scale ranging from 0 - 4 to indicate the degree of hazard.

Values: 0=Minimal 1=Slight 2=Moderate 3=Serious 4=Extreme

An asterisk(*) indicates chronic health hazards are associated with the chemical.

The proper protective equipment is identified with a letter corresponding to equipment listed after in parentheses.

Legend:

P273- Avoid release to the environment.

S61- Do not release product to the environment.

Do not handle until the Manufacturer's Safety Precautions have been read and understood. This data is up to the current level of our knowledge and experience. The safety data sheet is only intended to give a description of products with regard to safety requirements. However, it is not to be taken as a warranty or representation for which J&J Flooring Group or Pentz Commercial assumes legal responsibility. Any use of this information and data must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.