



Product Specifications

Construction	Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	15 oz./sy (509 grams/m2)
Pile Density	5216 oz./y3 (193.41 kg/m3)
Pattern Repeat	72.00" (w) x 24.00" (l) approx. (182.88cm x 60.96cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	10.17 stitches/in (4.00 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Encore® SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	53.9%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



2717 Authentic



2718 Central



2719 Essential



2720 Fundame...




2722 Innate



2723 Key



2726 Inherent



2728 True