



Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Patterned Loop |
| Backing | PremierBac® Plus |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 30 oz./sy (1017 grams/m2) |
| Pile Density | 7024 oz./y3 (260.45 kg/m3) |
| Pattern Repeat | 72.00" (w) x 77.40" (l) approx. (182.88cm x 196.60cm) |
| Gauge | 1/12 (4.72 rows/cm) |
| Stitches Per Inch | 12.3 stitches/in (4.84 stitches/cm) |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Encore® SD Ultima Fiber |
| Optional Warranties | Endure Plus TitanBac Plus Encore® 100 Fiber |


Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Indoor Air Quality | |
| Total Recycled Content | 47.9% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |


Colorways



2198 Mason



2200 Potter



2201 Weaver



2202 Woodwor...




2204 Painter



2205 Quilter



2206 Glassblow..



2207 Tailor



2210 Blacksmith



3316 Jeweler



3317 Carver



3318 Metalsmith