



**Installation Methods:** Parquet, Herringbone, Basketweave, Brick, Monolithic, Ashlar

#### Product Specifications

|                            |                                                                                                                                                                                                               |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>        | Tip Sheared Patterned Loop                                                                                                                                                                                    |
| <b>Backing</b>             | Nexus® Modular                                                                                                                                                                                                |
| <b>Dye Method</b>          | Solution Dyed                                                                                                                                                                                                 |
| <b>Fiber Type</b>          | Encore® SD Ultima® (with recycled content)                                                                                                                                                                    |
| <b>Face Weight</b>         | 20 oz./sy (678 grams/m2)                                                                                                                                                                                      |
| <b>Pile Density</b>        | 8141 oz./y3 (301.87 kg/m3)                                                                                                                                                                                    |
| <b>Pattern Repeat</b>      | N/A                                                                                                                                                                                                           |
| <b>Gauge</b>               | 1/12 (4.72 rows/cm)                                                                                                                                                                                           |
| <b>Stitches Per Inch</b>   | 10 stitches/in (3.94 stitches/cm)                                                                                                                                                                             |
| <b>Standard Size</b>       | 18" x 36" approx. (45.72cm x 91.44cm)                                                                                                                                                                         |
| <b>Standard Adhesive</b>   | Commercialon Premium Modular Adhesive                                                                                                                                                                         |
| <b>Optional Adhesive</b>   | TileTabs, Nexus Cushion Modular Adhesive, Advance Modular Carpet   Cushion Adhesive                                                                                                                           |
| <b>Standard Warranties</b> | <b>Nexus Modular</b><br><b>Commercialon Adhesive for Modular Carpet &amp; LVT</b><br><b>Encore® SD Ultima Fiber</b>                                                                                           |
| <b>Optional Warranties</b> | <b>Nexus Cushion Modular</b><br><b>Nexus FC Cushion</b><br><b>Advance Modular Backing</b><br><b>Tile Tabs</b><br><b>Nexus Cushion Adhesive</b><br><b>Advance Modular Adhesive</b><br><b>Encore® 100 Fiber</b> |

#### Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>ProTex® Soil Release</b>   | Standard |
| <b>Sentir® Odor-Blocker</b>   | Optional |

#### Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Indoor Air Quality</b>     | GLP9716                            |
| <b>Total Recycled Content</b> | 45.3%                              |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

#### Colorways



3758 Night Sha...



3759 Seaglass



3760 Pecan



3761 Dark Sage



3762 Silver Lin...



3763 Sand Dun...



3764 Ashwood



3765 Desert Gl...



3766 Celestial ...



3767 Greystone