



Installation Methods: Ashlar, Herringbone, 1/3 Drop

## 20 mil **Wear Layer** Thickness 5mm Finish / Coating Enhanced UV Urethane w/ Ceramic Bead Random Wood Pattern **Pattern Repeat Edge Treatment** 9" x 48" approx. (22.86cm x 121.92cm) Dimensions: Standard Adhesive Commercialon® LVT Adhesive **Backing Class** Commercial Grade **Commercial Traffic** Heavy Commercial Standard Warranties 15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

| Р | $\mathbf{a}$ | $\sim$ | V | $\mathbf{a}$ | $\cap$ | 1 | n | $\cap$ |
|---|--------------|--------|---|--------------|--------|---|---|--------|
|   |              |        |   |              |        |   |   |        |

| Sq.ft. per piece / carton | 3 / 24                   |
|---------------------------|--------------------------|
| Weight per piece / carton | 5.53 (lbs) / 44.25 (lbs) |
| Pieces per box            | 8                        |
| Boxes per pallet          | 52                       |

## Special Technologies

**Product Specifications** 

| Added Antimicrobial | ZPT (Zinc Protective Technology) |
|---------------------|----------------------------------|
|---------------------|----------------------------------|

## Environmental Specifications & Tests

| Indoor Air Quality        | FloorScore® Certified                                  |           |
|---------------------------|--|-----------|
| LEED v4                   | Contributes to IAQ: Low Emitting M                     | laterials |
| End of Life               | 100% Recyclable  |           |
| Class / ASTM F1700        | Class III Printed Film Vinyl Plank - Type B (embossed) |           |
| Radiant Panel             | Class 1  |           |
| ADA Compliance            | Compliant For Accessible Routes                        |           |
| ASTM F2055 (Size and Tole | Passes   |           |
| ASTM F386 (Thickness)     | Passes   |           |
| ASTM F1914 (Residual Inde | Passes   |           |
|                           | 5  |           |

ASTM F137 (Flexibility) Passes **ASTM F2199 (Dimensional Stability)** Passes **ASTM F925 (Chemical Resistance)** Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes ASTM E648 (Critical Radiant Flux) Passes **ASTM E662 (Optical Smoke Density)** Passes ASTM C1028 (Slip Resistance) Passes ASTM F970 (Static Load) Passes

Colorways



1010 Pier



1011 Header



1012 Anchor



1013 Brace



1014 Partition



1015 Beam