FLOORING

Koi Pond | 7725

Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

Construction	Multi-Level Tip Sheared Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	30 oz./sy (1017 grams/m2)
Pile Density	10228 oz./y3 (379.26 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	11 stitches/in (4.33 stitches/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	**Nexus Modular** **Commercialon Adhesive for Modular Carpet & LVT** **Encore® SD Ultima Fiber**
Optional Warranties	**Nexus Cushion Modular** **Nexus FC Cushion** **Advance Modular Backing** **Tile Tabs** **Encore® 100 Fiber**

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9716
Total Recycled Content	43.2%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

3798 Eucalyptus

3799 Harbor Mist

3800 Praline

3801 Canvas

3802 Burnished

3803 Moonstone

3804 Toasted P...

3805 Mulberry

3806 Inkwell

3807 Juniper