Commercialon Adhesive for Modular Carpet & LVT



Installation Methods: Parquet, Herringbone, Basketweave, Ashlar

20 mil **Wear Layer** Thickness 5mm Loose Lay Finish / Coating Enhanced UV Urethane w/ Ceramic Bead Random **Pattern Repeat Edge Treatment** Dimensions: 18" x 36" approx. (45.72cm x 91.44cm) Standard Adhesive Commercialon® LVT Adhesive **Backing Class** Commercial Grade **Commercial Traffic** Heavy Commercial

15 Year LVT

Packaging

Standard Warranties

Sq.ft. per piece / carton	4.5 / 27
Weight per piece / carton	8.3 (lbs) / 49.77 (lbs)
Pieces per box	6
Boxes per pallet	40

Special Technologies

Product Specifications

Added Antimicrobial	ZPT (Zinc Protective Technology)
---------------------	----------------------------------

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials	
End of Life	100% Recyclable	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Radiant Panel	Class 1	
ADA Compliance	Compliant For Accessible Routes	
ASTM F2055 (Size and Tolerance)		Passes
ASTM F386 (Thickness)		Passes
ASTM F1914 (Residual Indentation)		Passes
ASTM F137 (Flexibility)		Passes

ASTM F2199 (Dimensional Stability) Passes ASTM F925 (Chemical Resistance) Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes ASTM E648 (Critical Radiant Flux) Passes **ASTM E662 (Optical Smoke Density)** Passes ASTM C1028 (Slip Resistance) Passes ASTM F970 (Static Load) Passes

Colorways



1055 Saga



1056 Epic



1057 Tale



1058 Fable



1059 Fiction