



Product Specifications

Construction	Cut and Loop
Backing	Woven Synthetic
Dye Method	Solution Dyed
Fiber Type	PureColor® Nylon
Face Weight	32 oz./sy (1085 grams/m2)
Pile Density	3739 oz./y3 (138.64 kg/m3)
Pattern Repeat	36.00" (w) x 28.00" (l) approx. (91.44cm x 71.12cm)
Gauge	1/8 (3.15 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Living Spaces

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	47.2%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



9770 Pinehurst




9785 Cypress P...



9792 Augusta



9832 Pebble Be..



9925 Saw Grass



9945 Glen Abbey



9999 Sand Hills