## LVT





Installation Methods: Ashlar, Herringbone, 1/3 Drop

## Product Specifications

Commercial Traffic Heavy Commerc	-
	le
Backing Class Commercial Grad	
Standard Adhesive Commercialon®	LVT Adhesive
<b>Dimensions:</b> 9" x 48" approx.	(22.86cm x 121.92cm)
Pattern Repeat Random	
Finish / Coating Enhanced UV Ure	ethane w/ Ceramic Bead
Thickness 3mm	
Wear Layer 20 mil	

## Packaging

Sq.ft. per piece / carton	3 / 39	
Weight per piece / carton	3.05 (lbs) / 39.64 (lbs)	
Pieces per box	13	
Boxes per pallet	52	
Special Technologies	5	
Added Antimicrobial	ZPT (Zinc Protective Technol	ogy)
Environmental Speci	fications & Tests	
Indoor Air Quality	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials	
End of Life	100% Recyclable	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Radiant Panel	Class 1	
ADA Compliance	Compliant For Accessible Ro	utes
ASTM F2055 (Size and Tole	erance)	Passes
ASTM F386 (Thickness)		Passes
ASTM F1914 (Residual Ind	entation)	Passes
ASTM F137 (Flexibility)		Passes
ASTM F2199 (Dimensional Stability)		Passes
ASTM F925 (Chemical Resistance)		Passes
ASTM F1514 (Resistance to Heat)		Passes
ASTM F1515 (Resistance to Light)		Passes
ASTM E648 (Critical Radiant Flux)		Passes
ASTM E662 (Optical Smoke Density) Passes		Passes
ASTM C1028 (Slip Resistar	nce)	Passes
ASTM F970 (Static Load)		Passes

