



**Installation Methods:** Ashlar, Herringbone, 1/3 Drop

### Product Specifications

|                            |                                      |
|----------------------------|--------------------------------------|
| <b>Wear Layer</b>          | 20 mil                               |
| <b>Thickness</b>           | 5mm Loose Lay                        |
| <b>Finish / Coating</b>    | Enhanced UV Urethane w/ Ceramic Bead |
| <b>Pattern Repeat</b>      | Random                               |
| <b>Dimensions:</b>         | 9" x48"                              |
| <b>Standard Adhesive</b>   | Commercialon® LVT Adhesive           |
| <b>Backing Class</b>       | Commercial Grade                     |
| <b>Commercial Traffic</b>  | Heavy Commercial                     |
| <b>Standard Warranties</b> | <b>10 Year LVT</b>                   |

### Packaging

|                                  |                          |
|----------------------------------|--------------------------|
| <b>Sq.ft. per piece / carton</b> | 3 / 24                   |
| <b>Weight per piece / carton</b> | 5.53 (lbs) / 44.25 (lbs) |
| <b>Pieces per box</b>            | 8                        |
| <b>Boxes per pallet</b>          | 52                       |


### Special Technologies

|                            |                                  |
|----------------------------|----------------------------------|
| <b>Added Antimicrobial</b> | ZPT (Zinc Protective Technology) |
|----------------------------|----------------------------------|


### Environmental Specifications & Tests

|   |  |
|---|--|
| <b>Indoor Air Quality</b>                 | FloorScore® Certified                                  |
| <b>LEED v4</b>                            | Contributes to IAQ: Low Emitting Materials             |
| <b>End of Life</b>                        | 100% Recyclable  |
| <b>Class / ASTM F1700</b>                 | Class III Printed Film Vinyl Plank - Type B (embossed) |
| <b>Radiant Panel</b>                      | Class 1  |
| <b>ADA Compliance</b>                     | Compliant For Accessible Routes                        |
| <b>ASTM F2055 (Size and Tolerance)</b>    | Passes   |
| <b>ASTM F386 (Thickness)</b>              | Passes   |
| <b>ASTM F1914 (Residual Indentation)</b>  | Passes   |
| <b>ASTM F137 (Flexibility)</b>            | Passes   |
| <b>ASTM F2199 (Dimensional Stability)</b> | Passes   |
| <b>ASTM F925 (Chemical Resistance)</b>    | Passes   |
| <b>ASTM F1514 (Resistance to Heat)</b>    | Passes   |
| <b>ASTM F1515 (Resistance to Light)</b>   | Passes   |
| <b>ASTM E648 (Critical Radiant Flux)</b>  | Passes   |
| <b>ASTM E662 (Optical Smoke Density)</b>  | Passes   |
| <b>ASTM C1028 (Slip Resistance)</b>       | Passes   |
| <b>ASTM F970 (Static Load)</b>            | Passes   |

### Colorways




1063 Shadow




1064 Smoke



1065 Charcoal



1066 Sapphire




1067 Cobalt




1068 Denim



1069 Lime




1070 Fern




1071 Iris



1072 Marigold



1073 Tangerine



1074 Candy