I V/T



**Installation Methods:** Parquet, Herringbone, Basketweave, Brick, Monolithic, Ashlar

### **Product Specifications**

Wear Layer	20 mil
Thickness	3mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random
Edge Treatment	N/A
Dimensions:	18" x 36" approx. (45.72cm x 91.44cm)
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

# Packaging

4.5 / 45
4.52 (lbs) / 45.19 (lbs)
10
50

# Special Technologies

ASTM F1515 (Resistance to Light)

ASTM E648 (Critical Radiant Flux)

ASTM C1028 (Slip Resistance)

ASTM F970 (Static Load)

**ASTM E662 (Optical Smoke Density)** 

Added Antimicrobial	ZPT (Zinc Protective Technology)
---------------------	----------------------------------

# Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials	
End of Life	100% Recyclable	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Radiant Panel	Class 1	
ADA Compliance	Compliant For Accessible Routes	
ASTM F2055 (Size and Tolerance)		Passes
ASTM F386 (Thickness)		Passes
ASTM F1914 (Residual Indentation)		Passes
ASTM F137 (Flexibility)		Passes
ASTM F2199 (Dimensional Stability)		Passes
ASTM F925 (Chemical Resistance)		Passes
ASTM F1514 (Resistance to Heat)		Passes

### Colorways



1120 Agate

Passes

Passes

Passes

Passes

Passes