



## Product Specifications

<b>Construction</b>	Textile Composite
<b>Backing</b>	Kinetex Felt Cushion
<b>Dye Method</b>	Solution Dyed
<b>Wear Layer</b>	Polyester - Applied Pattern
<b>Pattern Repeat</b>	N/A
<b>Total Weight</b>	4.5 oz - 5.2 oz/ square foot
<b>Total Thickness</b>	.205 inches
<b>Dimensions:</b>	24" x 24" modules
<b>Standard Adhesive</b>	Kinetex Adhesive
<b>Packaging</b>	18 modules per box (72 sq.ft)
<b>Standard Warranties</b>	<b>Kinetex Adhesive</b> <b>Kinetex</b>

























## Special Technologies

## Environmental Specifications & Tests

<b>Carbon Footprint:</b>	Carbon Neutral
<b>Recyclability:</b>	100% Closed-loop Recyclable
<b>NSF 140:</b>	Platinum Certified
<b>Indoor Air Quality</b>	GLP2690
<b>Total Recycled Content:</b>	47%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

**Installation Methods:** Ashlar, Quarter Turn

## Colorways

					
100 Pattern	102 Moving	103 Optical	104 Physics	105 Motion	106 Blur
					
107 Slight	108 Superposing	109 Artifact	110 Mathematics	111 Halftone	112 Speedup
					
113 Drawing	114 Scanning	115 Broadband	116 Layers*	117 Shape*	118 Universal*
					
119 Hidden	120 Graphics	122 Transparen..	124 Art*	125 Phase	126 Objects