LVT



Installation Methods: Ashlar, 1/3 Drop, Herringbone

Product Specifications

Wear Layer	20 mil
Thickness	2.5mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random Wood Pattern
Edge Treatment	None
Dimensions:	6" x 48" approx. (15.24cm x 121.92cm)
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

Packaging

Sq.ft. per piece / carton	2 / 36
Weight per piece / carton	2.05 (lbs) / 36.97 (lbs)
Pieces per box	18
Boxes per pallet	60

Special Technologies


Added Antimicrobial	Yes	

Environmental Specifications & Tests

Environmental specifications & rests				
Indoor Air Quality	FloorScore® Certified			
LEED v4	Contributes to IAQ: Low Emitting Materials			
End of Life	100% Recyclable			
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)			
Radiant Panel	Class 1			
ADA Compliance	Compliant For Accessible Routes			
ASTM F2055 (Size and Tolerance)		Passes		
ASTM F386 (Thickness)		Passes		
ASTM F1914 (Residual Indentation)		Passes		
ASTM F137 (Flexibility)		Passes		
ASTM F2199 (Dimensional Stability)		Passes		
ASTM F925 (Chemical Resistance)		Passes		
ASTM F1514 (Resistance to Heat)		Passes		
ASTM F1515 (Resistance to Light)		Passes		

Colorways







1093 Preserve



1094 Habitat



ASTM E648 (Critical Radiant Flux)

ASTM C1028 (Slip Resistance)

ASTM F970 (Static Load)

ASTM E662 (Optical Smoke Density)



1095 Settlement 1096 Residency

Passes

Passes

Passes

Passes