

Installation Methods: Ashlar, Herringbone, 1/3 Drop

# **Product Specifications**

Wear Layer	20 mil
Thickness	5mm Loose Lay
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random
Dimensions:	9" x 48" approx. (22.86cm x 121.92cm)
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

### Packaging

Sq.ft. per piece / carton	3 / 24
Weight per piece / carton	5.53 (lbs) / 44.25 (lbs)
Pieces per box	8
Boxes per pallet	52

## Special Technologies

### Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials	
End of Life	100% Recyclable	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Radiant Panel	Class 1	
ADA Compliance	Compliant For Accessible Routes	
ASTM F2055 (Size and Tolerance)		Passes
ASTM F386 (Thickness)		Passes
ASTM F1914 (Residual Indentation)		Passes
ASTM F137 (Flexibility)		Passes
ASTM F2199 (Dimensional Stability)		Passes

#### **ASTM F925 (Chemical Resistance)** Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes ASTM E648 (Critical Radiant Flux) Passes **ASTM E662 (Optical Smoke Density)** Passes ASTM C1028 (Slip Resistance) Passes ASTM F970 (Static Load) Passes

## Colorways



1080 Knowledge



1081 Advantage



1082 Situation



1083 Information 1084 Leverage





1085 Dominance



1086 Influence