

Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications

Wear Layer	20 mil
Thickness	5mm Loose Lay
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random
Dimensions:	9" x 48" approx. (22.86cm x 121.92cm)
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

Packaging

Sq.ft. per piece / carton	3 / 24
Weight per piece / carton	5.53 (lbs) / 44.25 (lbs)
Pieces per box	8
Boxes per pallet	52

Special Technologies

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials	
End of Life	100% Recyclable	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Radiant Panel	Class 1	
ADA Compliance	Compliant For Accessible Routes	
ASTM F2055 (Size and Tolerance)		Passes
ASTM F386 (Thickness)		Passes
ASTM F1914 (Residual Indentation)		Passes
ASTM F137 (Flexibility)		Passes
ASTM F2199 (Dimensional Stability)		Passes

ASTM F925 (Chemical Resistance) Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes ASTM E648 (Critical Radiant Flux) Passes **ASTM E662 (Optical Smoke Density)** Passes ASTM C1028 (Slip Resistance) Passes ASTM F970 (Static Load) Passes

Colorways



1080 Knowledge



1081 Advantage



1082 Situation



1083 Information 1084 Leverage





1085 Dominance



1086 Influence