LV



Installation Methods: Ashlar, Herringbone, 1/3 Drop

## **Product Specifications Wear Layer** 20 mil **Thickness** 3mm Finish / Coating Enhanced UV Urethane w/ Ceramic Bead Pattern Repeat Random Wood Pattern **Edge Treatment** Micro Bevel Dimensions: 9" x 48" approx. (22.86cm x 121.92cm) Standard Adhesive Commercialon® LVT Adhesive **Backing Class** Commercial Grade **Commercial Traffic** Heavy Commercial Standard Warranties 15 Year LVT Commercialon Adhesive for Modular Carpet & Packaging Sq.ft. per piece / carton 3/39 3.05 (lbs) / 39.64 (lbs) Weight per piece / carton Pieces per box 13 52 Boxes per pallet

## **Environmental Specifications & Tests Indoor Air Quality** FloorScore® Certified LEED v4 Contributes to IAQ: Low Emitting Materials **End of Life** 100% Recyclable Class / ASTM F1700 Class III Printed Film Vinyl Plank - Type B (embossed) **Radiant Panel ADA Compliance** Compliant For Accessible Routes ASTM F2055 (Size and Tolerance) Passes ASTM F386 (Thickness) Passes ASTM F1914 (Residual Indentation) Passes Passes ASTM F137 (Flexibility) ASTM F2199 (Dimensional Stability) Passes **ASTM F925 (Chemical Resistance)** Passes

ZPT (Zinc Protective Technology)

Special Technologies

Added Antimicrobial

ASTM F1514 (Resistance to Heat)

ASTM F1515 (Resistance to Light)

**ASTM E648 (Critical Radiant Flux)** 

ASTM C1028 (Slip Resistance)

ASTM F970 (Static Load)

**ASTM E662 (Optical Smoke Density)** 





Passes

Passes

Passes

Passes

Passes

Passes