J+J FLOORING

Rhythm | 7502

Installation Methods: Brick, Ashlar, Quarter Turn

Product Specifications

Construction	Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	16 oz./sy (543 grams/m2)
Pile Density	5709 oz./y3 (211.69 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs, Advance Modular Carpet | Cushion Adhesive, Nexus Cushion Modular Adhesive
Standard Warranties	**Nexus Modular** **Commercialon Adhesive for Modular Carpet & LVT** **Encore® SD Ultima Fiber**
Optional Warranties	**Nexus Cushion Modular** **Nexus FC Cushion** **Advance Modular Backing** **Tile Tabs** **Nexus Cushion Adhesive** **Advance Modular Adhesive** **Encore® 100 Fiber**

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9716
Total Recycled Content	46.3%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

3633 Moonstone

3634 Toasted A...



3635 Cinder Sm..

3636 Sandlewo...

3637 Marine

3638 Baltic

3639 Inkwell

3640 Nightfall