




Installation Methods: Parquet, Herringbone, Basketweave, Brick, Monolithic, Ashlar

Colorways



1117 Fragments



1118 Mosaic

Product Specifications

| | |
|----------------------------|---|
| Wear Layer | 20 mil |
| Thickness | 3mm |
| Finish / Coating | Enhanced UV Urethane w/ Ceramic Bead |
| Pattern Repeat | Random |
| Edge Treatment | N/A |
| Dimensions: | 18" x 36" approx. (45.72cm x 91.44cm) |
| Standard Adhesive | Commercialon® LVT Adhesive |
| Backing Class | Commercial Grade |
| Commercial Traffic | Heavy Commercial |
| Standard Warranties | 15 Year LVT Commercialon Adhesive for Modular Carpet & LVT |

Packaging

| | |
|----------------------------------|--------------------------|
| Sq.ft. per piece / carton | 4.5 / 45 |
| Weight per piece / carton | 4.52 (lbs) / 45.19 (lbs) |
| Pieces per box | 10 |
| Boxes per pallet | 50 |

Special Technologies

| | |
|----------------------------|----------------------------------|
| Added Antimicrobial | ZPT (Zinc Protective Technology) |
|----------------------------|----------------------------------|

Environmental Specifications & Tests

| | |
|---|--|
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Class / ASTM F1700 | Class III Printed Film Vinyl Plank - Type B (embossed) |
| Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |
| ASTM F2055 (Size and Tolerance) | Passes |
| ASTM F386 (Thickness) | Passes |
| ASTM F1914 (Residual Indentation) | Passes |
| ASTM F137 (Flexibility) | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance) | Passes |
| ASTM F1514 (Resistance to Heat) | Passes |
| ASTM F1515 (Resistance to Light) | Passes |
| ASTM E648 (Critical Radiant Flux) | Passes |
| ASTM E662 (Optical Smoke Density) | Passes |
| ASTM C1028 (Slip Resistance) | Passes |
| ASTM F970 (Static Load) | Passes |