LV7



Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications Wear Layer 12 mil 2.5mm Thickness Finish / Coating Enhanced UV Urethane w/ Ceramic Bead Random Wood Pattern Pattern Repeat **Edge Treatment** 9" x 48" approx. (22.86cm x 121.92cm) Dimensions: Commercialon® LVT Adhesive Standard Adhesive **Backing Class** Commercial Grade **Commercial Traffic** Light Commercial Standard Warranties Commercialon Adhesive for Modular Carpet & 7 Year LVT Packaging Sq.ft. per piece / carton 2.55 (lbs) / 40.78 (lbs) Weight per piece / carton Pieces per box 16 52 Boxes per pallet Special Technologies **Added Antimicrobial** ZPT (Zinc Protective Technology) **Environmental Specifications & Tests Indoor Air Quality** FloorScore® Certified LEED v4 Contributes to IAQ: Low Emitting Materials **End of Life** 100% Recyclable Class / ASTM F1700 Class III Printed Film Vinyl Plank - Type B (embossed) **Radiant Panel ADA Compliance** Compliant For Accessible Routes ASTM F2055 (Size and Tolerance) Passes ASTM F386 (Thickness) Passes ASTM F1914 (Residual Indentation) Passes ASTM F137 (Flexibility) Passes **ASTM F2199 (Dimensional Stability)** Passes **ASTM F925 (Chemical Resistance)** Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes

Colorways



1000 Notable





1007 Curio



ASTM E648 (Critical Radiant Flux)

ASTM C1028 (Slip Resistance)

ASTM F970 (Static Load)

ASTM E662 (Optical Smoke Density)

1008 Paradigm



1060 Inheritance



Passes

Passes

Passes

Passes

1108 Occupy



1109 Manor



1110 Spread