## LVT

Colorways

## Step by Step 3mm | V5043



**Installation Methods:** Parquet, Herringbone, Basketweave, Brick, Ashlar

## Product Specifications

Wear Layer	20 mil		
Thickness	3mm	3mm	
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead		
Pattern Repeat	Random		
Edge Treatment	none		
Dimensions:	18" x 36" approx. (45.72cm x 91.44cm)		
Standard Adhesive	Commercialon® LVT Adhesive		
Backing Class	Commercial Grade		
Commercial Traffic	Heavy Commercial		
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT		
Packaging			
Sq.ft. per piece / carton	4.5 / 45		
Weight per piece / carton	4.52 (lbs) / 45.19 (lbs)		
Pieces per box	10		
Boxes per pallet	50		
Special Technologies	5		
Added Antimicrobial	ZPT (Zinc Protective Techno	blogy)	
Environmental Speci	fications & Tests		
Indoor Air Quality	FloorScore® Certified		
LEED v4	Contributes to IAQ: Low Emitting Materials		
End of Life	100% Recyclable		
Radiant Panel	Class 1		
ADA Compliance	Compliant For Accessible Re	outes	
ASTM F2055 (Size and Tole	erance)	Passes	
ASTM F386 (Thickness)		Passes	
ASTM F1914 (Residual Indentation)		Passes	
ASTM F137 (Flexibility)		Passes	
ASTM F2199 (Dimensional Stability)		Passes	
ASTM F925 (Chemical Resistance)		Passes	
ASTM F1514 (Resistance to Heat)		Passes	
ASTM F1515 (Resistance to Light)		Passes	
ASTM E648 (Critical Radiant Flux)		Passes	
ASTM E662 (Optical Smoke Density)		Passes	
ASTM C1028 (Slip Resistance)		Passes	
ASTM F970 (Static Load)		Passes	

1121 All Purpose 1122 Sheer 1123 Common ... 1124 Violet 1125 Iron Garnet 1126 Garnet 1128 Natural 1129 Egg Shell 1130 Shadow 1131 Sky Blue 1132 Sky 1127 Oatmeal 1133 Blue Denim 1134 Denim 1135 Lime Green 1136 Limeade 1137 Forest Wa.. 1138 Forest