



Product Specifications

| | |
|----------------------------|---------------------------------------|
| Construction | Direct Digital Print & Emboss SPC |
| Backing | DLVT Attached Cushion |
| Wear Layer | Equivalent to 20 mil |
| Attached Pad | 1.0 mm XPO |
| Locking Mechanism | One2Click® |
| Thickness | 5mm |
| Finish / Coating | Evertuff Clearcoat® |
| Pattern | 35 Unique Planks |
| Dimensions: | 7" x 48" approx. (17.78cm x 121.92cm) |
| Backing Class | Commercial Grade |
| Commercial Traffic | Light Commercial |
| Standard Warranties | Rigid Core |

Packaging

| | |
|----------------------------------|--------------------------|
| Sq.ft. per piece / carton | 2.22 / 22.17 |
| Weight per piece / carton | 3.75 (lbs) / 37.51 (lbs) |
| Pieces per box | 10 |
| Boxes per pallet | 50 |

Special Technologies

| | |
|---|--|
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |
| ASTM F2055 (Size and Tolerance) | Passes |
| ASTM F386 (Thickness) | Passes |
| ASTM F1914 (Residual Indentation) | Passes |
| ASTM F137 (Flexibility) | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance) | Passes |
| ASTM F1514 (Resistance to Heat) | Passes |
| ASTM F1515 (Resistance to Light) | Passes |
| ASTM E648 (Critical Radiant Flux) | Passes |
| ASTM E662 (Optical Smoke Density) | Passes |
| ASTM C1028 (Slip Resistance) | Passes |
| ASTM F970 (Static Load) | Passes |

Colorways



1195 Embellish



1196 Fusion



1197 Combinat...



1198 Mash Up



1199 Collage



1200 Alliance



1201 Hybrid



1202 Patch Work



1203 Unification