# LVT



Installation Methods: Parquet

# **Product Specifications**

Wear Layer	20 mil	
Thickness	5mm	
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead	
Edge Treatment	None	
Dimensions:	18" x 36" approx. (45.72cm x 91.44cm)	
Standard Adhesive	Commercialon® LVT Adhesive	
Backing Class	Commercial Grade	
Commercial Traffic	Heavy Commercial	
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT	

### Packaging

Sq.ft. per piece / carton	4.5 / 27
Weight per piece / carton	8.3 (lbs) / 49.77 (lbs)
Pieces per box	6
Boxes per pallet	40

## Special Technologies

Environmental Specifications & Tests			
Indoor Air Quality	FloorScore® Certified		
LEED v4	Contributes to IAQ: Low Emitting Materials		
End of Life	100% Recyclable		
Radiant Panel	Class 1		
ADA Compliance	Compliant For Accessible Routes		
ASTM F2055 (Size and Tolerance)		Passes	
ASTM F386 (Thickness)		Passes	
ASTM F1914 (Residual Indentation)		Passes	
ASTM F137 (Flexibility)		Passes	
ASTM F2199 (Dimensional Stability)		Passes	
ASTM F925 (Chemical Resistance)		Passes	
ASTM F1514 (Resistance to Heat)		Passes	
ASTM F1515 (Resistance to Light)		Passes	
ASTM E648 (Critical Radiant Flux)		Passes	

Colorways






1022 Wabi



1018 Kyoto



1023 Zen



**ASTM E662 (Optical Smoke Density)** 

ASTM C1028 (Slip Resistance)

ASTM F970 (Static Load)

1019 Edo



1020 Rush



Passes

Passes

Passes

1021 Goza