LVT



Installation Methods: Parquet, Herringbone, Basketweave, Brick, Monolithic, Ashlar

20 mil **Wear Layer** Thickness 5mm Finish / Coating Enhanced UV Urethane w/ Ceramic Bead **Pattern Repeat** Random **Edge Treatment** N/A 18" x 36" approx. (45.72cm x 91.44cm) **Dimensions:** Standard Adhesive Commercialon® LVT Adhesive **Backing Class** Commercial Grade **Commercial Traffic** Heavy Commercial 15 Year LVT Standard Warranties Commercialon Adhesive for Modular Carpet & LVT

ac	kag	ing		

Product Specifications

Sq.ft. per piece / carton	4.5 / 27
Weight per piece / carton	8.3 (lbs) / 49.77 (lbs)
Pieces per box	6
Boxes per pallet	40

Special Technologies

Added Antimicrobial	ZPT (Zinc Protective Technology)
Audeu Alltilliciobiai	Zi i (Ziiic i lotective lecililology)

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified		
LEED v4	Contributes to IAQ: Low Emitting Materials		
End of Life	100% Recyclable		
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)		
Radiant Panel	Class 1		
ADA Compliance	Compliant For Accessible Routes		
ASTM F2055 (Size and Tolerance)		Passes	
ASTM F386 (Thickness)		Passes	
ASTM F1914 (Residual Indentation)		Passes	

ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes

Colorways



1119 Pebble