



Product Specifications

Construction	Direct Digital Print & Emboss SPC	
Backing	DLVT Attached Cushion	
Wear Layer	Equivalent to 20 mil	
Attached Pad	1.0 mm XPO	
Locking Mechanism	One2Click®	
Thickness	5mm	
Finish / Coating	Evertuff Clearcoat®	
Pattern	35 Unique Planks	
Dimensions:	7" x 48" approx. (17.78cm x 121.92cm)	
Backing Class	Commercial Grade	
Commercial Traffic	Light Commercial	
Standard Warranties	Rigid Core	
Packaging		
Sq.ft. per piece / carton	2.22 / 22.17	

3.75 (lbs) / 37.51 (lbs)

Special Technologies

Weight per piece / carton

Pieces per box

Boxes per pallet

Environmental Specifications & Tests

10

50

Indoor Air Quality	FloorScore® Certified	FloorScore® Certified	
LEED v4	Contributes to IAQ: Low Emitting Materials		
End of Life	100% Recyclable		
Radiant Panel	Class 1		
ADA Compliance	Compliant For Accessible Routes		
ASTM F2055 (Size an	d Tolerance)	Passes	
ASTM F386 (Thickness)		Passes	
ASTM F1914 (Residual Indentation)		Passes	
ASTM F137 (Flexibility)		Passes	
ASTM F2199 (Dimensional Stability)		Passes	
ASTM F925 (Chemical Resistance)		Passes	
ASTM F1514 (Resistance to Heat)		Passes	
ASTM F1515 (Resistance to Light)		Passes	
ASTM E648 (Critical Radiant Flux)		Passes	
ASTM E662 (Optical Smoke Density)		Passes	
ASTM C1028 (Slip Resistance)		Passes	
ASTM F970 (Static Load)		Passes	

Colorways



1151 Inspire



1157 Network



1152 Transition



1158 Culture



1154 Mix



1159 Fuse



1155 Merge



1156 Combine