



Product Specifications

<b>Construction</b>	Multi-Level Tip Sheared Loop
<b>Backing</b>	PremierBac® Plus
<b>Dye Method</b>	Beck Dyed
<b>Fiber Type</b>	Type 6,6 Nylon
<b>Face Weight</b>	32 oz./sy (1085 grams/m2)
<b>Pile Density</b>	5760 oz./y3 (213.58 kg/m3)
<b>Pattern Repeat</b>	24.00" (w) x 28.00" (l) approx. (60.96cm x 71.12cm)
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Stitches Per Inch</b>	12.5 stitches/in (4.92 stitches/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>PremierBac Plus</b> <b>Commercialon Premium Broadloom Adhesive</b> <b>Commercialon Premium Seam Sealer</b> <b>Type 6,6 Nylon Fiber</b>
<b>Optional Warranties</b>	<b>Endure Plus</b> <b>TitanBac Plus</b>

Special Technologies

<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional

Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Indoor Air Quality</b>	GLP5055
<b>Total Recycled Content</b>	36.3%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 4 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

Colorways

 354 Indigo	 356 Mollusk	 358 Tahini	 359 Clove	 360 Chicory	 363 Clay
 369 Cochineal	 900 Mink	 901 Fossil	 903 Terra	 904 Teak	 905 Sesame
 907 Tea	 910 Palm	 911 Dill	 912 Ore	 913 Shale	 914 Glacier
 915 Wenge	 916 Shade	 917 Tusk	 918 Shitake	 919 Truffle	 920 Oyster
 921 Dusk					