

INVISION

LIVING SPACES COLLECTION *Rooms Carpet*

**FAIRWAY / LINKS / RANGE**





---

From our establishment in 1957, we have become one of the oldest exclusive manufacturers of *commercial flooring* in the United States. As one of the largest privately held mills, our FAMILY-OWNERSHIP provides a *heritage* of proven performance and expansive industry knowledge. Most importantly, our focus has always been on *people...* ensuring them that our products deliver the highest levels of BEAUTY, PERFORMANCE and DEPENDABILITY.

---

INVISION kinetex LVT



# fairway N9117 / links N9115



## fairway

Fairway offers a well-played balance of relaxed, easy patterning and follows through with on par, classic colorways. Fairway's irregular pattern and broadloom format adds sophistication to any residential type living space.



style N9117  
color 9770  
pinehurst



style N9117  
color 9785  
cypress point



style N9117  
color 9792  
augusta



style N9117  
color 9822  
oakmont



style N9117  
color 9832  
pebble beach



style N9117  
color 9945  
glen abbey



style N9117  
color 9950  
st. andrews

## links

Links offers a well-played balance of relaxed, easy patterning and follows through with on par, classic colorways. Links' structured grid-like pattern and broadloom format adds sophistication to any residential type living space.



style N9115  
color 9770  
pinehurst



style N9115  
color 9785  
cypress point



style N9115  
color 9792  
augusta



style N9115  
color 9822  
oakmont



style N9115  
color 9832  
pebble beach



style N9115  
color 9945  
glen abbey



style N9115  
color 9950  
st. andrews



Links Cypress Point.

# range N9116



Range Augusta.

## range

Range offers a well-played balance of relaxed, easy patterning and follows through with on par, classic colorways. Range's organic pattern and broadloom adds sophistication to any residential type living space.



style N9116  
color 9770  
pinehurst



style N9116  
color 9785  
cypress point



style N9116  
color 9792  
augusta



style N9116  
color 9822  
oakmont



style N9116  
color 9832  
pebble beach



style N9116  
color 9945  
glen abbey



style N9116  
color 9950  
st. andrews



Fairway Glenn Abbey.

## product details

### FIBER

**PureColor® Nylon** Our proven nylon brand for living spaces that represents the most comprehensive and affordable collection of quality, exceptional styling and unprecedented value currently available in the market.

### BACKINGS

#### **Woven Synthetic Backing System**

Superior construction to ensure dimensional stability for broadloom carpets.

#### OPTIONAL:

**TitanBac® Plus Moisture Barrier**

### ADHESIVES

#### **Commercialon® Premium Carpet Adhesive**

A premium carpet floor adhesive approved for all carpets and backing systems (except vinyl backed carpets). This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Group Carpet Installation Handbook. Commercialon Premium Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Adhesive is non toxic, has ultra-low odor and is antimicrobial in the dry state.

### TECHNOLOGIES

#### **Soil Release**

A fluorochemical technology that is applied and bonded to the pile fiber to impede soiling and to improve cleanability.

#### OPTIONAL:

**ProSept® Antimicrobial**

**Sentir® Advanced Odor-Blocking Technology**

### APPLICATION

Fairway, Links and Range are specifically designed and manufactured for residential use and are not designed for commercial applications. Installations in non-residential applications are excluded from warranty coverage.

## corporate programs



#### **Green Circle - Zero Waste to Landfill Operations Certification**

We are proudly certified as a Zero Waste to Landfill manufacturer by GreenCircle Certified, LLC., a prominent third-party certifier of environmental claims. We are the first commercial flooring manufacturer in the United States to achieve this landfill free status and the first company in the industry to have its waste diversion efforts audited and verified by a recognized, third-party certifier.

To learn more about zero waste or our other initiatives see our sustainability progress report online at [jjflooringgroup.com/sustainability](http://jjflooringgroup.com/sustainability)



**We're on it.**

The J+J Flooring Group Premium Customer Experience.

Our Premium Customer Experience is a carefully crafted process by which we guarantee that our customers will get the products, services and the reliability they expect from us.

To learn more visit [jjflooringgroup.com/about/cx](http://jjflooringgroup.com/about/cx)



*These products are specifically designed and manufactured for residential use and are not designed for commercial applications. Installations in non-residential applications are excluded from warranty coverage.*

| style                             | fairway N9117 broadloom  | links N9115 broadloom  | range N9116 broadloom  |
|-----------------------------------|--|--|--|
| construction                      | cut and loop   | cut and loop   | cut and loop   |
| fiber type                        | PureColor® Nylon   | PureColor® Nylon   | PureColor® Nylon   |
| dye method                        | solution dyed  | solution dyed  | solution dyed  |
| ounce weight                      | 32 oz/sy (1085 grams/m <sup>2</sup> )  | 32 oz/sy (1085 grams/m <sup>2</sup> )  | 32 oz/sy (1085 grams/m <sup>2</sup> )  |
| gauge                             | 1/8 (3.15 rows/cm)   | 1/8 (3.15 rows/cm)   | 1/8 (3.15 rows/cm)   |
| backing                           | woven synthetic  | woven synthetic  | woven synthetic  |
| size                              | 12 feet (3.66 m)   | 12 feet (3.66 m)   | 12 feet (3.66 m)   |
| pattern repeat                    | n/a  | n/a  | n/a  |
| total thickness (nominal average) | .375 inches (0.95 cm)  | .375 inches (0.95 cm)  | .375 inches (0.95 cm)  |
| special technology                | Soil Release   | Soil Release   | Soil Release   |
| optional special technologies     | ProSept® antimicrobial<br>Sentir® advanced odor blocking treatment   | ProSept® antimicrobial<br>Sentir® advanced odor blocking treatment   | ProSept® antimicrobial<br>Sentir® advanced odor blocking treatment   |
| physical testing                  | flooring radiant panel (class 1)<br>pill test (passes)<br>smoke density (less than 450 flaming)<br>static generation (less than 3.5 kv)<br>ADA compliance (compliant for accessible routes)  | flooring radiant panel (class 1)<br>pill test (passes)<br>smoke density (less than 450 flaming)<br>static generation (less than 3.5 kv)<br>ADA compliance (compliant for accessible routes)  | flooring radiant panel (class 1)<br>pill test (passes)<br>smoke density (less than 450 flaming)<br>static generation (less than 3.5 kv)<br>ADA compliance (compliant for accessible routes)  |
| application                       | rooms carpet/residential   | rooms carpet/residential   | rooms carpet/residential   |
| fiber warranties                  | 10 year stain resistance<br>10 year colorfastness<br>10 year pet stain resistance<br>10 year fiber performance for wear<br>10 year fiber performance for static  | 10 year stain resistance<br>10 year colorfastness<br>10 year pet stain resistance<br>10 year fiber performance for wear<br>10 year fiber performance for static  | 10 year stain resistance<br>10 year colorfastness<br>10 year pet stain resistance<br>10 year fiber performance for wear<br>10 year fiber performance for static  |
| backing warranties                | If installed using glue down installation method:<br>10 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>10 year against delamination<br><br>If installed using stretch -in installation method:<br>5 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>5 year against delamination | If installed using glue down installation method:<br>10 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>10 year against delamination<br><br>If installed using stretch -in installation method:<br>5 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>5 year against delamination | If installed using glue down installation method:<br>10 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>10 year against delamination<br><br>If installed using stretch -in installation method:<br>5 year tuft bind strength (edge ravel, yarn pulls, zippering)<br>5 year against delamination |

---

 FLOORING GROUP

[jjflooringgroup.com](http://jjflooringgroup.com)

P.O. Box 1287  
Dalton, GA 30722  
p 800 241 4586  
f 706 275 4433

INVISION kinetex LVT

---

A Division of **Engineered**  
FLOORS