

Convergent



Convergent



INSPIRATION

In the act of moving together, Convergent is a fusion of organic striations of dark and light, met with varying texture. This medley of technical innovation and beautiful design creates a fully organic and calm visual for the floor.







Convergent MODULAR + BROADLOOM



COLOR 3061
coincide



COLOR 3062
medley



COLOR 3063
synthesize



COLOR 3064
consolidate



COLOR 3067
meld



COLOR 3068
combine



COLOR 3069
incorporate



COLOR 3070
compose



COLOR 3071
blend



COLOR 3072
unify



COORDINATES

Beyond the beauty of individual products, our flooring coordinates effortlessly across all of our product platforms - modular carpet tile, broadloom, LVT and Kinetex textile composite flooring. This offering enables you to blend a range of designs with tonal simplicity to create palettes that reflect the demands of each unique space.

1. CONVERGENT // 3925 // #3070 Compose // Broadloom
2. NETWORK // 1842 // #2853 Cyber // Kinetex
3. TWILL WEAVE // 7586 // #2874 Mills // Modular
4. FRAMEWORK // V5001 // #1013 Brace // LVT
5. MODERN CLASSICS // V5002 // #1024 Charles // LVT
6. PUT A CORK IN IT // 1830 // #2197 Drum // Kinetex
7. CONVERGENT // 7925 // #3070 Compose // Modular
8. PROVISION // 1831 // #2277 Procurement // Kinetex
9. FRACTURED PLAID // 7587 // #2879 Percalé // Modular

FIBER

Nylon 6,6 fiber offers superior resistance to crushing, matting, wearing, soiling, staining and static with lifetime performance warranties for wear and static.

BACKINGS

Nexus® Modular products can be installed in a variety of ways and are performance engineered to be visually appealing. In addition, they are designed to accommodate your long-term flooring budget.

- » Manufactured in an ISO 14001 certified facility
- » Contains pre-consumer recycled content and contributes to LEED
- » Recyclable through the J+J Flooring’s R4 Carpet Reclamation Program

PremierBac® Plus is standard on broadloom products and provides superior construction to ensure solid dimensional stability for broadloom carpets.

- » Stretch-in or glue-down installation
- » Manufactured in an ISO 14001 certified facility
- » Contains pre-consumer recycled content and contributes to LEED
- » Recyclable through the J+J Flooring’s R4 Carpet
- » Reclamation Program

MOISTURE

Are high levels of moisture in your concrete slab causing issues with your project’s floor covering? We can help.

- » Nexus® Modular Carpet with TileTabs – 99% RH
- » Cost-efficient
- » Long-term performance
- » Straightforward, easy-to-understand Lifetime warranty
- » Requires no special floor preparation

ADHESIVE

Commercialon® Premium Carpet Adhesive is formulated for the most demanding interior carpet installations. It forms a powerful bond with stiff and heavy backed commercial carpets directly over approved substrates. It is quick setting, features antimicrobial protection and can be removed easily. This solvent free adhesive is also low in odor, meeting the low VOC emission criteria of the CRI Green Label Plus Indoor Air Quality. Commercialon Premium Adhesive is for use with broadloom PremierBac® Plus and Endure®Plus backing systems.

Commercialon® Premium Modular Adhesive A high strength acrylic latex-based carpet adhesive specifically formulated for bonding modular PVC backed carpet to the floor. This premium adhesive is for use with all Nexus Modular Tile products. This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Carpet Installation Handbook. Commercialon Premium Modular Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Modular Adhesive is non toxic, has ultra-low odor and is antimicrobial in the dry state.

OPTIONAL:
TileTabs - High Tack Adhesive Tabs (modular only)

TECHNOLOGIES

ProTex® Anti-Soil Treatment
ProTex is a proprietary anti-soil treatment technology that is applied and bonded to the pile fiber to impede soiling and to improve cleanability. It is standard on all J+J Flooring products.

OPTIONAL:
ProSept® Antimicrobial
Sentir® Advanced Odor-Blocking Technology

CORPORATE PROGRAMS



Green Circle Certification
J+J Flooring strives to manage, and ultimately eliminate, waste in our manufacturing processes. Our steadfast commitment in the pursuit of Zero Waste to Landfill has earned us the industry-leading level of 95% waste diversion certification by a third-party certifier.

To learn more about our waste initiatives, please see our Sustainability Report online at jfflooring.com/sustainability



We're on it.
The J+J Flooring Group Premium Customer Experience.

Our Premium Customer Experience is a carefully crafted process by which we guarantee that our customers will get the products, services and the reliability they expect from us. To learn more visit: jfflooring.com/customer-experience/

STRAIGHT-FORWARD WARRANTIES				
Warranty: Installed with TileTabs	Warranty: Installed with Commercialon® Premium Adhesive (non-prorated)	Warranty: Installed with any other adhesive	Max RH, pH: Installed without Commercialon® Premium Sealer	Max RH, pH: Installed with Commercialon® Premium Sealer
Lifetime	Lifetime	1 Year	90% RH, pH 9	99% RH, pH 11 (TileTabs) 97% RH, pH 11 (Commercialon® Adhesive)

STYLE

convergent 7925 modular

convergent 3925 broadloom

CONSTRUCTION

textured loop

textured loop

FIBER TYPE

Nylon 6,6

Nylon 6,6

DYE METHOD

beck dyed

beck dyed

OUNCE WEIGHT

28 oz./sy (949 grams/m2)

28 oz./sy (949 grams/m2)

GAUGE

1/10 (3.94 rows/cm)

1/10 (3.94 rows/cm)

BACKING

Nexus® modular

PremierBac® Plus

SIZE

12" x 48" (30.5 cm X 122.0 cm)

12 feet (3.66 m)

PATTERN REPEAT

n/a

n/a

TOTAL THICKNESS (nominal average)

0.250 inches (0.64 cm)

0.250 inches (0.64 cm)

SPECIAL TECHNOLOGY

ProTex® anti-soil treatment

ProTex® anti-soil treatment

OPTIONAL SPECIAL TECHNOLOGIES

ProSept® antimicrobial
Sentir® advanced odor blocking treatment

ProSept® antimicrobial
Sentir® advanced odor blocking treatment


PHYSICAL TESTING

flooring radiant panel (class 1)	flooring radiant panel (class 1)
pill test – (passes)	pill test – (passes)
smoke density (less than 450 flaming)	smoke density (less than 450 flaming)
static generation -(less than 3.5 kv)	static generation -(less than 3.5 kv)
ADA compliance (compliant for accessible routes)	ADA compliance (compliant for accessible routes)

WARRANTIES

lifetime fiber performance for wear	lifetime fiber performance for wear
lifetime fiber performance for static	lifetime fiber performance for static
lifetime for tuft bind strength (edge ravel, yarn pulls, zippering)	10 year for tuft bind strength (edge ravel, yarn pulls, zippering)
lifetime against delamination	10 year against delamination
lifetime dimensional stability	

MODULAR INSTALLATION METHODS



©2020 J+J Flooring Group, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law. Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not J+J Flooring's responsibility.



P.O. BOX 2207

DALTON, GA 30722

P 800 241 4586

F 706 275 4433

JJFLOORING.COM

carpet | lvt | kinetex



FLOORING
A DIVISION OF ENGINEERED FLOORS