

INVISION  
CRAFTWORK



From our establishment in 1957, we have become one of the oldest exclusive manufacturers of *commercial flooring* in the United States. As one of the largest privately held mills, our FAMILY-OWNERSHIP provides a *heritage* of proven performance and expansive industry knowledge. Most importantly, our focus has always been on *people...* ensuring them that our products deliver the highest levels of **BEAUTY**, **PERFORMANCE** and **DEPENDABILITY**.

---

INVISION **kinetex**

(cover) Craftwork *Glassblower*, broadloom.  
(right) Craftwork *Quilter*, brick.



*craftwork*

**SPECIFICATION**

<b>style</b>	craftwork 7099 modular	craftwork 6599 broadloom
<b>construction</b>	textured patterned loop	textured patterned loop
<b>fiber type</b>	100% Encore® SD Ultima nylon	100% Encore® SD Ultima nylon
<b>dye method</b>	solution dyed	solution dyed
<b>backing</b>	Nexus® modular	PremierBac® Plus
<b>ounce weight (nominal average)</b>	30.0 oz / square yard	30.0 oz / square yard
<b>total thickness (nominal average)</b>	0.312 inches (0.79 cm)	0.281 inches (0.71 cm)
<b>dimensions</b>	24" x 24" (61cm x 61 cm)	12 feet (3.66 m)



2198  
mason



2199  
sculptor



2200  
potter



2201  
weaver



2202  
woodworker



2203  
basketweaver



2204  
painter



2205  
quilter



2206  
glassblower



2207  
tailor



2208  
printmaker



2209  
calligrapher



2210  
blacksmith



[above] Craftwork *Glassblower & Potter*, monolithic. [center] Craftwork *Potter*, quarter turn. [right] Craftwork *Quilter*, quarter turn. [pages 8 & 9] Craftwork *Potter*, broadloom.



## product details

### FIBER

**Encore® SD Ultima®** (with recycled content) Encore SD Ultima is specifically engineered to maximize appearance retention with exceptional color, performance, sustainability and practicality.

### BACKINGS

#### Nexus® Modular

Nexus modular products can be installed in a variety of ways and are performance engineered to be visually appealing. In addition, they are designed to accommodate your long-term flooring budget.

- Manufactured in an ISO 14001 certified facility
- Contains pre-consumer recycled content and contributes to LEED
- Recyclable through the J+J Flooring Group's R4 Carpet Reclamation Program

#### PremierBac® Plus

J+J Flooring Group PremierBac® Plus is standard on Invision's broadloom products and provides superior construction to ensure solid dimensional stability for broadloom carpets.

- Stretch-in or glue-down installation
- Manufactured in an ISO 14001 certified facility
- Contains pre-consumer recycled content and contributes to LEED
- Recyclable through the J+J Flooring Group's R4 Carpet Reclamation Program

#### OPTIONAL:

TitanBac® Plus  
Endure® Plus

### ADHESIVES

#### Commercialon® Premium Carpet Adhesive

A premium carpet floor adhesive approved for all carpets and backing systems (except vinyl backed carpets). This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Group Carpet Installation Handbook. Commercialon Premium Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Adhesive is non toxic, has ultra-low odor and is antimicrobial in the dry state.

#### Commercialon® Premium Modular Adhesive

A high strength acrylic latex-based carpet adhesive specifically formulated for bonding modular PVC backed carpet to the floor. This premium adhesive is for use with all Invision Nexus Modular Tile products. This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Group Carpet Installation Handbook. Commercialon Premium Modular Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Modular Adhesive is non toxic, has ultra-low odor and is antimicrobial in the dry state.

#### OPTIONAL:

TileTabs - High Tack Adhesive Tabs (modular only)

### TECHNOLOGIES

#### ProTex® Soil Release

ProTex is a proprietary fluorochemical technology that is applied and bonded to the pile fiber to impede soiling and to improve cleanability. It is standard on all J+J Flooring Group products.

#### OPTIONAL:

ProSept® Antimicrobial  
Sentir® Advanced Odor-Blocking Technology

## corporate programs



### Green Circle - Zero Waste to Landfill Operations Certification

We are proudly certified as a Zero Waste to Landfill manufacturer by GreenCircle Certified, LLC., a prominent third-party certifier of environmental claims. We are the first commercial flooring manufacturer in the United States to achieve this landfill free status and the first company in the industry to have its waste diversion efforts audited and verified by a recognized, third-party certifier.

To learn more about zero waste or our other initiatives see our sustainability progress report online at [jjflooringgroup.com/sustainability](http://jjflooringgroup.com/sustainability)



We're on it.  
The J+J Flooring Group Premium Customer Experience.

Our Premium Customer Experience is a carefully crafted process by which we guarantee that our customers will get the products, services and the reliability they expect from us.

To learn more visit: [jjflooringgroup.com/customer-experience/](http://jjflooringgroup.com/customer-experience/)

©2017 J&J Flooring Group, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law.

Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer's, and not J+J Flooring Group's responsibility.


\*NRC rating is a measure of the effectiveness of a material in absorbing sound. The higher the NRC rating, the greater the ability of the flooring product to absorb airborne noise. Independent laboratory testing of Kinetex has shown an average NRC rating of 0.33 (bare concrete flooring will typically provide a NRC Rating of 0.015).

\*\*IIC is a rating of the insulation from impact noise. The higher the IIC rating, the greater the sound insulation. Independent laboratory testing of Kinetex has shown an average IIC Rating of .64 (bare concrete flooring will typically provide an IIC Rating of 34) NOTE: Test results and testing laboratory will vary, and the above information is not guaranteed.



style	craftwork 7099 modular	craftwork 6599 broadloom
construction	textured patterned loop	textured patterned loop
fiber type	100% Encore® SD Ultima® Nylon	100% Encore® SD Ultima® Nylon
dye method	solution dyed	solution dyed
ounce weight	30 oz/sy (1,017 grams/m <sup>2</sup> )	30 oz/sy (1,017 grams/m <sup>2</sup> )
gauge	1/12 (4.72 rows/cm)	1/12 (4.72 rows/cm)
backing	Nexus® modular	PremierBak® Plus
size	24" x 24"	12 feet
pattern repeat	n/a	80 x 77.4 inches
total thickness (nominal average)	.312 inches (0.79 cm)	.281 inches (0.71 cm)
special technology	ProTex® fluorochemical	ProTex® fluorochemical
optional special technologies	ProSept® antimicrobial Sentir® advanced odor blocking treatment	ProSept® antimicrobial Sentir® advanced odor blocking treatment
physical testing	flooring radiant panel – (class 1) pill test – (passes) smoke density – (less than 450 flaming) static generation – (less than 3.5 kv) ADA compliance – (compliant for accessible routes)	flooring radiant panel – (class 1) pill test – (passes) smoke density – (less than 450 flaming) static generation – (less than 3.5 kv) ADA compliance – (compliant for accessible routes)
warranties	lifetime fiber performance for wear lifetime fiber performance for static lifetime stain removal lifetime colorfastness to light and atmospheric contaminants lifetime for tuft bind strength (edge ravel, yarn pulls, zippering) lifetime against delamination lifetime dimensional stability	lifetime fiber performance for wear lifetime fiber performance for static lifetime stain removal lifetime colorfastness to light and atmospheric contaminants lifetime for tuft bind strength (edge ravel, yarn pulls, zippering) lifetime against delamination

#### installation methods



---

 **FLOORING GROUP**

[jjflooringgroup.com](http://jjflooringgroup.com)

P.O. Box 1287  
Dalton, GA 30722  
p 800 241 4586  
f 706 275 4433

**INVISION kinetex**

---

*A Division of* **Engineered  
FLOORS**