

Fairway II & Links II



Fairway II & Links II



INSPIRATION

We are drawn to what relaxes and restores us – to surround ourselves within a serene atmosphere that is essential to home life, as well as conducive to work life. Designed with that comfort factor in mind, Fairway II and Links II offer softly textured flooring to infuse interiors with warmth and style, for a beautifully understated, intimate vibe. Fairway II features a rich, lush texture with a relaxed neutral palette and is available in broadloom as well as a 24” x 24 modular tile. Links II enhances the visual and tactile appeal with its soft linear pattern and warm, welcoming feel. This broadloom’s organic colorways offer the perfect backdrop for inviting interiors.



[cover] FAIRWAY II // SAW GRASS // ashtar
[right] LINKS II // PEBBLE BEACH // broadloom



Fairway II

24"x24" MODULAR + BROADLOOM



COLOR 9770
pinehurst



COLOR 9785
cypress point



COLOR 9792
augusta



COLOR 9925
saw grass



COLOR 9832
pebble beach



COLOR 9945
glen abbey



COLOR 9999
sand hills



Links II

BROADLOOM



COLOR 9770
pinehurst



COLOR 9785
cypress point



COLOR 9792
augusta



COLOR 9925
saw grass



COLOR 9832
pebble beach



COLOR 9945
glen abbey



COLOR 9999
sand hills



LEGEND // FICTION // 1/3 drop // FAIRWAY II // PEBBLE BEACH // monolithic



Fairway II

COORDINATES

Beyond the beauty of individual products, our flooring coordinates effortlessly across all of our product platforms - modular carpet tile, broadloom, LVT and Kinetex textile composite flooring. This offering enables you to blend a range of designs with tonal simplicity to create palettes that reflect the demands of each unique space.

- 1. FRACTURED PLAID // 7587 // 2879 Percale // Modular
- 2. FAIRWAY II // N117 & N9117 // 9832 Pebble Beach // Modular + Broadloom
- 3. PUT A CORK IN IT // 1830 // 2188 Cask // Kinetex
- 4. ELEMENTAL // 7683 // 2635 Raw // Modular
- 5. STRIA // 7585 // 2747 Kashmir // Modular
- 6. LEGEND // V5010 //1059 Fiction // LVT
- 7. NETWORK // 1842 // 2854 Modem // Kinetex
- 8. FRAMEWORK // Framework V5001 // 1012 Anchor // LVT
- 9. TWILL WEAVE // 7586 // 2879 Percale // Modular



[above] **LINKS II** // SAW GRASS // broadloom // **TIMELESS** // GIFT // ashlar
[back cover] **FAIRWAY II** // SAND HILLS // broadloom



Links II

- 1. **TRANQUIL** // 7593 & 6593 // 3237 Smoke // Modular + Broadloom
- 2. **TIMELESS** // V5011 // 1061 Gift // LVT
- 3. **ORGANIC RAKU** // 7062 // 2345 Kiln // Modular
- 4. **PINNACLE II** // N9092 // 9925 Talus // Broadloom
- 5. **MINERAL** // 7027 // 1796 Granite // Modular
- 6. **LINKS II** // N9115 // 9925 Saw Grass // Broadloom
- 7. **OBSIDIAN** // 7718 // 2960 Feldspar // Modular
- 8. **ELEMENTAL** // 7683 // 2636 Pipes // Modular
- 9. **TATAMI** // V5003 // 1017 Nara // LVT
- 10. **SERENE** // 7592 & 6592 // 3237 Smoke // Modular + Broadloom

FIBER

PureColor® Nylon Our proven nylon brand for living spaces that represents the most comprehensive and affordable collection of quality, exceptional styling and unprecedented value currently available in the market.

BACKINGS

Woven Synthetic Backing System Superior construction to ensure dimensional stability for broadloom carpets.

Nexus® Modular products can be installed in a variety of ways and are performance engineered to be visually appealing. In addition, they are designed to accommodate your long-term flooring budget.

- » Manufactured in an ISO 14001 certified facility
- » Contains pre-consumer recycled content and contributes to LEED
- » Recyclable through the J+J Flooring’s R4 Carpet Reclamation Program

OPTIONAL:
TitanBac® Plus Moisture Barrier

ADHESIVE

Commercialon® Premium Carpet Adhesive
A premium carpet floor adhesive approved for all carpets and backing systems (except vinyl backed carpets). This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Carpet Installation Handbook. Commercialon Premium Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Adhesive is non toxic, has ultra- low odor and is antimicrobial in the dry state.

Commercialon® Premium Modular Adhesive
A high strength acrylic latex-based carpet adhesive specifically formulated for bonding modular PVC backed carpet to the floor. This premium adhesive is for use with all Nexus Modular Tile products. This adhesive is guaranteed for the lifetime of the installation when used in accordance with the J+J Flooring installation instructions. Commercialon® Premium Modular Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon® Premium Modular Adhesive is non toxic, has ultra-low odor and is antimicrobial in the dry state.

OPTIONAL:
Commercialon® High Moisture Adhesive
TileTabs® - High Tack Adhesive Tabs (modular only)

MOISTURE

Are high levels of moisture in your concrete slab causing issues with your project’s floor covering? We can help.

- » Nexus® Modular Carpet with TileTabs – 99% RH
- » Cost-efficient
- » Long-term performance
- » Straightforward, easy-to-understand warranty
- » Requires no special floor preparation

TECHNOLOGIES

ProTex® Anti-Soil Treatment is a proprietary anti-soil treatment technology that is applied and bonded to the pile fiber to impede soiling and to improve cleanability. It is standard on all J+J Flooring products.

OPTIONAL:
ProSept® Antimicrobial
Sentir® Advanced Odor-Blocking Technology

APPLICATION

Fairway II and Links II are specifically designed and manufactured for residential use and are not designed for commercial applications. Installations in non-residential applications are excluded from warranty coverage.

STYLE	links II N9115 broadloom	fairway II N9117 broadloom	fairway II N117 modular
CONSTRUCTION	cut and loop	cut and loop	cut and loop
FIBER TYPE	PureColor® Nylon	PureColor® Nylon	PureColor® Nylon
DYE METHOD	solution dyed	solution dyed	solution dyed
OUNCE WEIGHT	32.0 oz./sy (1085 grams/m²)	32.0 oz./sy (1085 grams/m²)	32.0 oz./sy (1085 grams/m²)
GAUGE	1/8 (3.15 rows/cm)	1/8 (3.15 rows/cm)	1/10 (3.94 rows/cm)
BACKING	woven synthetic	woven synthetic	Nexus® modular
SIZE	12 feet (3.66 cm)	12 feet (3.66 cm)	24” x 24” (61.0 cm x 61.0 cm)
PATTERN REPEAT	36” W x 28” L (91.44 cm x 71.12 cm)	36” W x 28” L (91.44 cm x 71.12 cm)	n/a
TOTAL THICKNESS (nominal average)	0.375 inches (0.95 cm)	0.375 inches (0.95 cm)	0.406 inches (1.031)
APPLICATION	rooms carpet/residential only	rooms carpet/residential only	rooms carpet/residential only
SPECIAL TECHNOLOGY	ProTex® Anti-Soil Treatment	ProTex® Anti-Soil Treatment	ProTex® Anti-Soil Treatment
OPTIONAL SPECIAL TECHNOLOGIES	ProSept® antimicrobial Sentir® advanced odor blocking treatment	ProSept® antimicrobial Sentir® advanced odor blocking treatment	ProSept® antimicrobial Sentir® advanced odor blocking treatment
PHYSICAL TESTING	flooring radiant panel (class 1) pill test – (passes) smoke density (less than 450 flaming) static generation (less than 3.5 kv) ADA compliance (compliant for accessible routes)	flooring radiant panel (class 1) pill test – (passes) smoke density (less than 450 flaming) static generation (less than 3.5 kv) ADA compliance (compliant for accessible routes)	flooring radiant panel (class 1) pill test – (passes) smoke density (less than 450 flaming) static generation (less than 3.5 kv) ADA compliance (compliant for accessible routes)
FIBER WARRANTIES	10 year stain resistance 10 year colorfastness 10 year pet stain resistance 10 year fiber performance for wear 10 year fiber performance for static	10 year stain resistance 10 year colorfastness 10 year pet stain resistance 10 year fiber performance for wear 10 year fiber performance for static	10 year stain resistance 10 year colorfastness 10 year pet stain resistance 10 year fiber performance for wear 10 year fiber performance for static
BACKING WARRANTIES	<i>If installed using glue down installation method:</i> 10 year tuft bind strength (edge ravel, yarn pulls, zippering) 10 year against delamination <i>If installed using stretch-in installation method:</i> 5 year tuft bind strength (edge ravel, yarn pulls, zippering) 5 year against delamination	<i>If installed using glue down installation method:</i> 10 year tuft bind strength (edge ravel, yarn pulls, zippering) 10 year against delamination <i>If installed using stretch-in installation method:</i> 5 year tuft bind strength (edge ravel, yarn pulls, zippering) 5 year against delamination	lifetime for tuft bind strength (edge ravel, yarn pulls, zippering) lifetime against delamination lifetime dimensional stability

MODULAR INSTALLATION METHODS



ashlar



brick



monolithic



quarter turn

STRAIGHT-FORWARD WARRANTIES					
Warranty: Installed with TileTabs	Warranty: Installed with Commercialon® Premium Adhesive and Commercialon® High Moisture Adhesive (non-prorated)	Warranty: Installed with any other adhesive	Max RH, pH: Installed without Commercialon® Premium Sealer	Max RH, pH: Installed with Commercialon® Premium Sealer	Max RH, pH: Installed with Commercialon® High Moisture Adhesive
Lifetime	Lifetime	1 Year	90% RH, pH 9	99% RH, pH 11 (TileTabs) 97% RH, pH 11 (Commercialon® Adhesive)	99% RH, pH12



©2023 J+J Flooring Group, LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law. Due to the unique visual characteristics of modular carpets, pattern repeats and pattern run-off seams may appear more noticeable than in broadloom carpets. Such visual characteristics do not constitute a manufacturing defect, and as such, should be considered when selecting modular carpet and its installation.

These photographs are representations of the installation for this modular product. Your modular installation may look different than these photos depending upon individual tile placement, lighting, and overall space layout, including furnishings. Final tile placement and the resulting visual is thus the customer’s, and not J+J Flooring’s responsibility.



P.O. BOX 2207

DALTON, GA 30722

P 800 241 4586

F 706 275 4433

JJFLOORING.COM

carpet | lvt | kinetex



FLOORING
A DIVISION OF ENGINEERED FLOORS