

# Kinetex® Adhesive

Kinetex® Adhesive non-PVC Adhesive is an aggressive, pressure sensitive adhesive designed for the installation of Kinetex® textile composite flooring. Kinetex Adhesive is non-flammable and is both water and alkali resistant when dry. It has low odor and "zero" calculated VOC's, which makes it ideal for use in schools, health care facilities, public buildings, and anywhere odor is a concern.

## Advantages

- May be used for on or above grade installations over concrete subfloors
- MicroSept™ Antimicrobial Protection
- CRI Green Label Plus™ certified
- Meets or exceeds California South Coast Air Quality Management District (SCAQMD) Rule 1168

## Application

- 1/16"x1/16"x1/16" U or square notch trowel (maximum of 720 square feet per 4-gallon pail)
- Adhesive must be full spread, do not use the grid method. Allow to completely dry until transparent, or does not transfer to finger when touched. Drying time will vary with temperature, humidity and air velocity; however, do not allow adhesive to dry for more than two hours before installing floor covering. Roll with a 75 or 100 pound carpet roller upon completion (depending on the type of floor covering being installed). See Kinetex Installation Instructions.

## Substrates

Kinetex Adhesive can be applied over a variety of porous and non-porous surfaces including: steel, terrazzo, APA approved plywood, raised access panel and properly prepared concrete (above, or below grade in the absence of excessive alkali or moisture). Wood floors must receive a roll-on application of Commercialon® Premium Sealer.

The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65°- 95° F, and the humidity below 65% for 48 hours prior to, during, and after the testing and installation. See Kinetex Installation Instructions

Substrates must be structurally sound, smooth, dry and free of dust, dirt, wax, paint, grease, curing agents, unapproved sealers, old adhesives and foreign matter. Concrete floors must be fully cured and dry. Refer to the ACI Committee 302.1 04R Report.

## Clean Up

Wet adhesive may be removed with warm soapy water. Dampen white cotton toweling and blot to remove (do not rub). Dried adhesive may be removed using the same dampen and blot technique with safety solvent.

## Limitations

For professional use only. Not for use where high alkalinity conditions exist.

## Warranty

For complete warranty information regarding Kinetex Adhesive, or if you have questions regarding the use of this product:

### J+J Flooring products:

J+J Flooring P.O. Box 1287 Dalton, Georgia 30722-1287  
800.241.4586

### EF Contract products:

EF Contract 1502 Coronet Drive Dalton, Georgia 30720  
800.451.1250

## Shelf Life

One year from manufacturing date, in an unopened container. Protect from freezing.

This adhesive is not photochemically reactive as defined by California Rules 102 and 443.

## For more information, technical or installation questions contact:

### J+J Flooring products:

J+J Flooring  
P.O. Box 1287  
Dalton, Georgia 30722-1287  
800.241.4586

### EF Contract products:

EF Contract  
1502 Coronet Drive  
Dalton, Georgia 30720  
800.451.1250