

Pinnacle II Summit II



INSPIRATION

Good room design promotes a positive mood – a cozy nook you look forward to relaxing and retreating to - a place you can unwind in. Pinnacle II and Summit II were designed to meet the need for warm, welcoming spaces with soothing colorways and plush textures that create a calming and serene residential retreat.





Pinnacle II

BROADLOOM



COLOR 9858 granite



COLOR 9930 slope



COLOR 9810 meadow



COLOR 9925 talus



COLOR 9779 canyon



COLOR 9969 point



Summit II

BROADLOOM



COLOR 9785 limestone



COLOR 9792



COLOR 9791 frost



COLOR 9925 plateau



COLOR 9770 peak



COLOR 9945 dome





Pinnacle II

COORDINATES

Beyond the beauty of individual products, our flooring coordinates effortlessly across all of our product platforms - modular carpet tile, broadloom, LVT and Kinetex textile composite flooring. This offering enables you to blend a range of designs with tonal simplicity to create palettes that reflect the demands of each unique space.

- 1. OBSIDIAN // 7718 // 3279 Feldspar Marine // Modular
- 2. TRANQUIL // 7593 // 3228 Sky // Modular or Broadloom
- 3. PINNACLE II // N9092 // 9930 Slope // Broadloom
- 4. SERENE // 6592 // 3228 Sky // Modular or Broadloom
- 5. METAMORPHIC // 7717 // 2960 Feldspar // Modular
- 6. LEGEND // V5010 // 1059 Fiction // LVT
- 7. PROVISION // 1831 // 2276 Fare // Kinetex
- 8. FAIRWAY II // N9117 // 9832 Pebble Beach // Modular or Broadloom
- 9. OBSIDIAN // 7718 // 2960 Feldspar // Modular

7





Summit II

COORDINATES

- 1. LINKS II // N9115 // 9925 Saw Grass // Broadloom
- 2. FRAMEWORK // V5001 // 1014 Partition // LVT
- 3. ADJUST // 7601 // 3273 Light Beam // Modular
- 4. TWILL WEAVE // 7586 // 2874 Mills // Modular
- 5. BOUCLÉ // 3081 // 2704 Varigated // Modular and Broadloom
- 6. SUMMIT II // N9086 // 9925 Plateau // Broadloom
- 7. NETWORK // 1842 // 2853 Cyber // Kinetex
- 8. STRIA // 7585 // 2742 Pima // Modular
- 9. FRACTURED PLAID // 7587 // 2874 Mills // Modular
- 10. METAMORPHIC // 7717 // 2968 Talc // Modular

9

PRODUCT DETAILS

FIBER

PureColor® Nylon is our proven nylon brand for living spaces that represents the most comprehensive and affordable collection of quality, exceptional styling and unprecedented value currently available in the market.

BACKINGS

Woven Synthetic Backing System offers superior construction to ensure dimensional stability for broadloom carpets.

OPTIONAL:

TitanBac® Plus Moisture Barrier

APPLICATION

Pinnacle II and Summit II are specifically designed and manufactured for residential use and are not designed for commercial applications. Installations in non-residential applications are excluded from warranty coverage.

ADHESIVE

Commercialon® Premium Carpet Adhesive

is a premium carpet floor adhesive approved for all carpets and backing systems (except vinyl backed carpets). This adhesive is guaranteed for the life of the installation when used in accordance with the J+J Flooring Carpet Installation Handbook. Commercialon Premium Adhesive meets the CRI Low-VOC Emission Criteria, CRI ID# PSA-425402. Commercialon Premium Adhesive is non toxic, has ultralow odor and is antimicrobial in the dry state.

TECHNOLOGIES

ProTex® Anti-Soil Treatment is a proprietary anti-soil treatment technology that is applied and bonded to the pile fiber to impede soiling and to improve cleanability. It is standard on all J+J Flooring products.

OPTIONAL:

ProSept® Antimicrobial Sentir® Advanced Odor-Blocking Technology

| STYLE | pinnacle II N9092 broadloom | summit II N9086 broadloom |
|-----------------------------------|--|--|
| CONSTRUCTION | cut and loop | cut pile |
| FIBER TYPE | PureColor® Nylon | PureColor® Nylon |
| DYE METHOD | solution dyed | solution dyed |
| OUNCE WEIGHT | 28.0 oz./sy(949 grams/m²) | 30.0 oz./sy(1017 grams/m²) |
| GAUGE | 1/8 (3.15 rows/cm) | 1/10 (3.94 rows/cm) |
| BACKING | woven synthetic | woven synthetic |
| SIZE | 12 feet (3.66 cm) | 12 feet (3.66 cm) |
| PATTERN REPEAT | n/a | n/a |
| TOTAL THICKNESS (nominal average) | 0.375 inches (0.953 cm) | 0.375 inches (0.953 cm) |
| APPLICATION | rooms carpet/residential only | rooms carpet/residential only |
| SPECIAL TECHNOLOGY | ProTex® anti-soil treatment | ProTex® anti-soil treatment |
| OPTIONAL SPECIAL | ProSept® antimicrobial | ProSept® antimicrobial |
| TECHNOLOGIES | Sentir® advanced odor blocking treatment | Sentir® advanced odor blocking treatment |
| PHYSICAL TESTING | flooring radiant panel – (class 1) | flooring radiant panel – (class 1) |
| | pill test – (passes) | pill test – (passes) |
| | smoke density – (less than 450 flaming) | smoke density – (less than 450 flaming) |
| | static generation – (less than 3.5 kv) | static generation – (less than 3.5 kv) |
| | ADA compliance – (compliant for accesible routes) | ADA compliance – (compliant for accesible routes) |
| FIBER WARRANTIES | 10 year stain resistance | 10 year stain resistance |
| | 10 year colorfastness | 10 year colorfastness |
| | 10 year pet stain resistance | 10 year pet stain resistance |
| | 10 year fiber performance for wear | 10 year fiber performance for wear |
| | 10 year fiber performance for static | 10 year fiber performance for static |
| BACKING WARRANTIES | If installed using glue down installation method: | If installed using glue down installation method: |
| | 10 year tuft bind strength (edge ravel, yarn pulls, zippering) | 10 year tuft bind strength (edge ravel, yarn pulls, zippering) |
| | 10 year against delamination | 10 year against delamination |
| | If installed using stretch-in installation method: | If installed using stretch-in installation method: |
| | 5 year tuft bind strength (edge ravel, yarn pulls, zippering) | 5 year tuft bind strength (edge ravel, yarn pulls, zippering) |
| | 5 year against delamination | 5 year against delamination |



©2021 Engineered Floors LLC - This unique design is protected under the U.S. Copyright Act of 1976. Any unauthorized copying or duplication of this design constitutes copyright infringement in violation of federal law.

10



P.O. BOX 2207

DALTON, GA 30722

P 800 241 4586

F 706 275 4433

JJFLOORING.COM

