



Commercialon® Premium Carpet Seam Sealer

Product Identification

Product Class: Aqueous Adhesive

Product Name: Premium Carpet Seam Sealer Trade Name: Commercialon® Seam Sealer

Hazardous Ingredients

None known.

*All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).

Physical Data

Boiling Point: 212° F

Vapor Density: Same as water. Evaporation Rate: Same as water.

Appearance and Odor: White, milky opague low odor

Weight per Gallon: 8.4 lbs.

Percent Volatile by Weight: 29-32% (as water)

Solubility in Water: Dispersible V.O.C. (Calculated): "zero" grams/liter

Fire and Explosion Hazard Data

Flammable Limits: Non-flammable

Flash Point: > 212 deg. F.

Flammability Classification: OSHA: None, DOT: None Extinguishing Media: CO2, chemical foam, water fog

Special Fire Fighting Features

Wear self-contained breathing gear when in confined area.

Health Hazard Data

Threshold Limit Value: Not established

 $\hbox{ Effects of Overexposure: } No\ known\ chronic\ overexposure \\$

effects.



Emergency and First Aid Procedure

Eye contact may cause irritation. In case of eye contact, flush with water for 10–15 minutes. If irritation persists, consult a physician.

Skin Contact: prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.

Inhalation: if symptomatic, move to fresh air. Get medical attention if symptoms occur.

Reactivity Data

Conditions to Avoid: Excessive heat or cold.

Stability: Stable.

Incompatibility: None known.

Hazardous Decomposition Products: None known;

Normal (CO2, CO).

Hazardous Polymerization: Will not occur.

Precautions for Handling and Use

Ventilation: Local ventilation.

Protective Gloves: Recommended.

Eye Protection: Safety glasses.

Hygienic Practices: Wash with soap and water after exposure. Respiratory Protection: Not required with adequate ventilation.

Other Protective Equipment: None.

Spills: Cover small spills with inert absorbent, then sweep up and place in waste disposal container. Dispose of in accordance with Federal, State and Local regulations.

Special Precautions/Other Comments

Precautions to be taken in handling and storing: Store inside at a temperature of 60° - 100° F. Do not allow product to freeze.

Other precautions: None

Transportation Data

D.O.T. Hazard Class: Unregulated

24-Hour Emergency

Chemtrec: 800 424 9300

J+J Flooring Customer Relations Department at 800.241.4586

EF Contract Customer Relations Department at 800.451.1250

Pentz Commercial Technical Relations Department at 866.706.974